

RUSH

THE COMFORT OF PANORAMIC VISION

Available in twilight version, the panoramic and lightweight RUSH model offers perfect optical quality, permanent comfort and modern design.



RUSHPSI



RUSHPSF



RUSHDPI



RUSHTWI



* RUSHKITFS
Foam & Strap Kit (The
foam is compatible with
RUSH & RUSH+ Models
// The strap is only com-
patible with RUSH+)



25 g

SUPPLIED WITH

Adjustable cord
CORDC



+ UPPER PROTECTION













+ ADJUSTABLE NON-SLIP BRIDGE

+ NON-SLIP TEMPLES

bollé
SAFETY

RUSH

THE COMFORT OF PANORAMIC VISION

| MODEL | VERSIONS | REFERENCES | LENS MARKING | FRAME MARKING | COATINGS |
|-------|--|------------|--|---|--------------------------|
| RUSH |  Clear | RUSHPSI | 2C-1,2  1 FT €€ |  EN166 FT €€ | Anti-scratch/anti-fog |
| |  Smoke | RUSHPSF | 5-3,1  1 FT €€ |  EN166 FT €€ | Anti-scratch/anti-fog |
| |  HD | RUSHDPI | 2C-1,2  1 FT €€ |  EN166 FT €€ | Hydrophobic/anti-scratch |
| |  Twilight | RUSHTWI | 5-2  1 FT €€ |  EN166 FT €€ | Anti-scratch/anti-fog |
| | * Foam & Strap Kit | RUSHKITFS | - | - | - |

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

- F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.
- T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

€€ European standard  Manufacturer name

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

€€ European standard  Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

TECHNOLOGY

BHD

A revolutionary coating for exceptional clarity and light transmission. Its visible light transmission rate is 96% compared with 90% for conventional clear lenses.

B-TWILIGHT

the new B-twilight technology offers the advantages of ESP with a double anti-fog coating (on both sides of the lenses) to prevent fogging in the most challenging conditions. Designed and used in low light conditions, it improves contrast. Its light transmission rate is perfect for outdoors, particularly early morning and late evening. B-Twilight filters 76% of blue light.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE

| | RUSHDPI | RUSHPSI | RUSHPSF | RUSHTWI | RUSHKITFS |
|--------------------------------------|---------------|---------------|---------------|---------------|---------------|
| Individual plastic bag | 3660740000097 | 3660740006648 | 3660740006655 | 3660740006662 | 3660740006488 |
| 10 safety spectacles per inner box | 3660740100094 | 3660740106645 | 3660740106652 | 3660740106669 | 3660740106485 |
| 240 safety spectacles per outer pack | 3660740200091 | 3660740206642 | 3660740206659 | 3660740206666 | 3660740206482 |

CHARACTERISTICS

| | |
|--------------|-----------------------|
| LENSES | PC - 2,2 mm - Curve 9 |
| FRAME | PC + PVC |
| STRAP | Non applicable |
| FOAM | SBR |
| SPARE LENSES | No |



18/09/2014

Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle
SAFETY